

# Highly efficient flue gas analyzer

**testo 320 – Just a few “clicks” away from a heating system diagnosis**

---

High-resolution colour graphic display

---

Quick and easy menu structure

---

Storage space for 500 measurement values

---

Measurement of flue gas, draught, pressure, ambient CO, differential temperature and gas leak detection

---

O<sub>2</sub> and CO sensor and flue gas probe with temperature probe

---

TÜV-tested according to EN 50379, Parts 1-3



The new testo 320 is a high-quality measuring instrument for efficient flue gas analysis. Its wide measuring range makes it a reliable partner for eliminating malfunctions and emergencies, monitoring legal limit values or for daily routine work servicing heating systems. The numerous measurement menus of the testo 320 are clearly structured.



- O<sub>2</sub>
- CO<sub>2</sub>
- CO
- hPa
- qA
- Eta
- °C

Standardized menu procedures, which are stored in the instrument specifically for your country, simplify operation – depending on which standards you are dealing with. The high-resolution display allows a detailed presentation of the measurement procedures and is easily legible even under the worst conditions.

# Product properties

**High-resolution colour graphic display**  
The measurement menus and measurement values are presented in detail and always easily legible.

177,3 °c  
12,17 % CO  
6,3 % qA

**Sensor monitoring**  
Integrated traffic light system which continuously monitors the sensor functionality.




**Fast sensor zeroing**  
Automatic zeroing of the sensor in only 30 seconds after start-up, and which can be cancelled if not required.




**Sensors exchangeable by the user**  
Easy exchange of sensors by the user – no adjustment necessary.



**Memory**  
Up to 500 measurement protocols can be saved and called up in the memory of the testo 320.



**Lithium battery**  
Operation with a Lithium battery (1500mAh) – no battery change necessary, up to eight hours running time, charging via USB connection possible.



**Attachment**  
Integrated magnets for fast attachment to burner/boiler.



**Stamp of approval**

The flue gas analyzer testo 320 is TÜV-tested according to EN 50379, Parts 1-3.

**Robust design**

Robust, durable instrument – ideally suited even to rough surroundings.

**Condensate trap**

Integrated condensate trap – very easily emptied.

**Efficient exchange of probes**

Fast and easy exchange of probes via the probe coupling. All gas paths are connected to the instrument at once with the bayonet connection.

**Probe filter**

Easy exchange of probe filter.

**Flexibility with modular probes**

A range of probe lengths and diameters ensure a high degree of flexibility for all applications. To exchange the probe shaft, it is simply placed on the probe handle and engages.

## Ordering data / Accessories

### testo 320 set for heating constructors

0632 3220	testo 320 with H <sub>2</sub> -compensated CO sensor
0554 1105	USB mains unit
0516 3300	System case (height: 130 mm)
0554 0549	Testo fast printer IRDA
0600 9741	Compact flue gas probe (length 300 mm, Ø 6 mm)
0600 9787	Combustion air probe (length 190 mm)



#### Measuring instrument with options

	Part no.
testo 320 flue gas analyzer, incl. O <sub>2</sub> sensor, calibration protocol, graphic display	0632 3220
Option CO sensor without H <sub>2</sub> -compensation	
Option H <sub>2</sub> -compensated CO sensor	
Option CO <sub>low</sub> sensor	
Bluetooth option	

#### Spare gas sensors

	Part no.
Spare sensor O <sub>2</sub> for testo 320	0393 0005
Spare CO sensor (without H <sub>2</sub> -compensation) for testo 320	0393 0053
Spare CO sensor H <sub>2</sub> -compensated for testo 320	0393 0105
Spare CO <sub>low</sub> sensor for testo 320	0393 0103

Smoke tester with oil and soot sheet, for measuring soot in flue gas, excl. cone (part no. 0554 9010)

0554 0307

Testo Bluetooth®/IRDA printer incl. 1 roll of printer paper, rechargeable battery and mains unit

0554 0620

Testo fast printer IrDA with wireless infrared interface; 1 roll thermal paper; 4 AA batteries

0554 0549

Spare thermal paper for printer, permanent ink

0554 0568

PC analysis software easyheat, for presenting measurement procedures as diagrams, tables and for managing customer data

0554 3332

USB mains unit incl. cable

0554 1105

Spare battery

0515 5046

Instrument case (height: 130 mm) for instrument, probes and accessories

0516 3300

Instrument case with double base (height: 180 mm) for instrument, probes and accessories

0516 3301

ISO calibration certificate/flue gas

0520 0003

# Probes

## Compact basic flue gas probes

	Part no.
Flue gas probe compact; length 180 mm; Ø 6 mm; Tmax. 500 °C; probe stop; NiCr-Ni thermocouple, 2.2 m hose and particle filter included	0600 9740
Flue gas probe compact; length 300 mm; Ø 6 mm; Tmax. 500 °C; probe stop; NiCr-Ni thermocouple, 2.2 m hose and particle filter included	0600 9741

## Modular flue gas probes

	Part no.
Flue gas probe modular, incl. cone for attachment; thermocouple NiCr-Ni; hose 2.2 m; particle filter; length 180 mm; Ø 8 mm; Tmax. 500 °C; TÜV-tested	0600 9760
Flue gas probe; length 300 mm; Ø 8 mm; Tmax. 500 °C; TÜV approval; probe stop; NiCr-Ni thermocouple; 2.2 m hose and particle filter included	0600 9761
Flue gas probe; length 180 mm; Ø 6 mm; Tmax. 500 °C; probe stop; NiCr-Ni thermocouple; 2.2 m hose and particle filter included	0600 9762
Flue gas probe; length 300 mm; Ø 6 mm; Tmax. 500 °C; probe stop; NiCr-Ni thermocouple; 2.2 m hose and particle filter included	0600 9763
Flue gas probe flexible; thermocouple NiCr-Ni; hose 2.2 m; dirt filter; length 330 mm; Ø 9 mm; Tmax. 180 °C; short-term 200 °C; ideal for measuring at inaccessible points	0600 9770

## Probe accessories

	Part no.
Probe shaft; length 180 mm; 8 mm; Tmax. 500 °C	0554 9760
Probe shaft; length 300 mm; Ø 8 mm; Tmax. 500 °C	0554 9761
Probe shaft flexible; length 330 mm; Ø 9 mm; Tmax. 180 °C	0554 9770
Probe shaft multi-hole; length 300 mm; Ø 8 mm; for mean CO calculation	0554 5762
Probe shaft multi-hole; length 180 mm; Ø 8 mm; for mean CO calculation	0554 5763
Hose extension; 2.8 m; extension cable for probe	0554 1202
Hose connection set with adapter for separate gas pressure measurement	0554 1203
Spare dirt filter, modular probe; 10 off	0554 3385
Spare particle filter, compact probe; 10 off	0554 0040

# Probes

## Additional probes

	Part no.
Dual wall clearance probe for O <sub>2</sub> supply air measurement	0632 1260
Gas leak detection probe; 0 to 10000 ppm CH <sub>4</sub> /C <sub>3</sub> H <sub>8</sub>	0632 3330
Ambient CO probe, for detecting CO in buildings and rooms; 0 to +500 ppm	0632 3331
Differential temperature set; consisting of 2 Velcro probes and temperature adapter	0554 1208
Fine pressure probe: highly accurate probe for the measurement of differential pressure and temperature, as well as Pitot tube measurement of flow velocities (see technical data)	0638 0330
Capillary hose set for 4 Pa measurement	0554 1215

## Combustion air temperature probes

	Part no.
Combustion air temperature probe, immersion depth 190 mm	0600 9787
Combustion air temperature probe, immersion depth 60 mm	0600 9797

## Additional temperature probes

	Part no.
Mini ambient air probe; for separate ambient air temperature measurement; 0 to +80 °C	0600 3692
Very fast reaction surface probe	0604 0194
Connection cable	0430 0143

# Technical data

	<b>Measuring range</b>	<b>Accuracy <math>\pm 1</math> digit</b>	<b>Resolution</b>	<b>Adjustment time <math>t_{90}</math></b>
<b>Temperature</b>	-40 to +1200 °C	$\pm 0.5$ °C (0 to +100.0 °C) $\pm 0.5$ % of m.v. (remaining range)	0.1 °C (-40 to +999,9 °C) 1 °C (> +1000 °C)	
<b>Draught measurement</b>	-9.99 to +40 hPa	$\pm 0.02$ hPa or $\pm 5$ % of m.v. (-0.50 to +0.60 hPa) $\pm 0.03$ hPa (+0.61 to +3.00 hPa) $\pm 1.5$ % of m.v. (+3.01 to +40.00 hPa)	0.01 hPa with fine draught option 0.001 hPa	
<b>Pressure measurement</b>	0 to +300 hPa	$\pm 0.5$ hPa (0.0 to 50.0 hPa) $\pm 1$ % of m.v. (50.1 to 100.0 hPa) $\pm 1.5$ % of m.v. (remaining range)	0.1 hPa with fine draught option 0.01 hPa	
<b>O<sub>2</sub> measurement</b>	0 to 21 Vol. %	$\pm 0.2$ Vol. %	0.1 Vol. %	< 20 s
<b>CO measurement (without H<sub>2</sub>-compensation)</b>	0 to 4000 ppm	$\pm 20$ ppm (0 to 400 ppm) $\pm 5$ % of m.v. (401 to 2000 ppm) $\pm 10$ % of m.v. (2001 to 4000 ppm)	1 ppm	< 60 s
<b>CO measurement (H<sub>2</sub>-compensated)</b>	0 to 8000 ppm	$\pm 10$ ppm or $\pm 10$ % of m.v. (0 to 200 ppm) $\pm 20$ ppm or $\pm 5$ % of m.v. (201 to 2000 ppm) $\pm 10$ % of m.v. (2001 to 8000 ppm)	1 ppm	< 40 s
<b>Determination of degree of effectivity (Eta)</b>	0 to 120%		0.1%	
<b>Flue gas loss</b>	0 to 99.9%		0.1%	
<b>CO<sub>2</sub> determination</b> digital calculation from O <sub>2</sub>	Display range 0 to CO <sub>2</sub> max	$\pm 0.2$ Vol. %	0.1 Vol. %	< 40 s
<b>Option CO<sub>low</sub> measurement (H<sub>2</sub>-compensated)</b>	0 to 500 ppm	$\pm 2$ ppm (0 to 39.9 ppm) $\pm 5$ % of m.v. (remaining range)	0.1 ppm	
<b>Ambient CO measurement (with CO probe)</b>	0 to 500 ppm	$\pm 5$ ppm (0 to 100 ppm) $\pm 5$ % of m.v. (> 100 ppm)	1 ppm	
<b>Gas leak measurement for flammable gases (with gas leak detection probe)</b>	Display range 0 to 10.000 ppm CH <sub>4</sub> / C <sub>3</sub> H <sub>8</sub>	Signal optical display (LED) audible signal via buzzer		< 2 s
<b>Ambient CO<sub>2</sub> measurement (with ambient CO<sub>2</sub> probe)</b>	0 to 1 Vol. % 0 to 10.000 ppm	$\pm 50$ ppm or $\pm 2$ % of m.v. (0 to 5000 ppm) $\pm 100$ ppm or $\pm 3$ % of m.v. (5001 to 10000 ppm)		
<b>Differential pressure, flow velocity and temperature via fine pressure probe</b>	$\pm 10.000$ Pa  0.15 to 3 m/s max. -40 to +1,200 °C (dependent on probe)	$\pm 0.3$ Pa (0 to 9.99 Pa) plus $\pm 1$ Digit $\pm 3$ % of m.v. (10 to 10.000 Pa) plus $\pm 1$ Digit  $\pm 0.5$ °C (-40 to 100 °C) $\pm 0.5$ % of m.v. (rem. measuring range) plus probe accuracy	0.1 m/s 0.1 °C	

## General technical data

Storage temperature	-20 to +50 °C	Display	Colour graphic display 240 x 320 pixels
Operating temperature	-5 to +45 °C	Weight	573 g
Power supply	Battery: 3.7 V / 2,400 mAh Mains unit: 6 V / 1.2 A	Dimensions	240 x 85 x 65 mm
Memory	500 measurement values	Guarantee	Instrument/probe/gas sensors: 24 months Thermocouple/rech. battery: 12 months <a href="https://www.testo.com/guarantee">https://www.testo.com/guarantee</a>
		Guarantee conditions	

testo 320

Be sure.  testo

0981 2884/msp/I/01.2020

Subject to change without notice.

[www.testo.com](http://www.testo.com)