

Waterproof surface probe with widened measurement tip for fl... - with wider measuring tip

Waterproof surface probe with widened measurement tip for flat surfaces, T/C Type T



Technical data

Temperature - TC Type T (Cu-CuNi)

Measuring range	-58.0° to 662.0 °F / -50 to +350 °C
Accuracy	±0.4 °F (-4.0° to 158.0 °F) / ±0.2 °C (-20 to +70 °C) Class 1 (Remaining Range) ¹⁾
Reaction time	30 sec

1) According to standard EN 60584-2, the accuracy of Class 1 refers to -40 to +350 °C (Type T).

General technical data

Weight	3.95 oz. / 112 g
Dimensions	51 in. / 1300 mm
Length probe shaft tip	1.969 in. / 50 mm
Diameter probe shaft	0.197 in. / 5 mm
Diameter probe shaft tip	0.236 in. / 6 mm
Cable length	3.773 ft. / 1.15 m
Fixed cable	yes
Protection class	IP65
Housing	ABS / TPE / PUR
Length probe shaft	4.528 in. / 115 mm
Product colour	white; silver

Delivery Scope:

1 x waterproof surface probe (TC type T) with fixed cable (cable length 1.2 m).

Waterproof

Thermocouple type T

Measuring range: -50 to +350 °C